

# Preco 200 Series Compact Back-up Alarm

## Field Proven Reliability



### Description

Field proven reliability has thrust the 200 Series alarms into the highest demand category of any low sound level alarm on the market. Used by major OEMs. These 200 Series alarms are available with terminal studs or wire leads and are available with or without self grounding strap.

### Features and Benefits

Specialty 200 Series Alarms:

- Model 270 (pictured): This compact, high sound level alarm is specifically designed for 107 db. The solid state alarm is polarity protected and it's self resonating circuitry automatically adjusts to environment conditions to ensure a constant 107 db output.
- Model 240CS: The Night Silent Alarm is designed for use at nighttime in sound sensitive areas as mandated. The feature disengages the back alarm when voltage is applied to the blue wire either via a dash mount toggle or wired to headlights.
- Model ELT: The ELT248, ELT278 and ELT280 are specifically designed as low sound level alarms for electric powered vehicles.
- Model FS232: This dual alarm is designed for use in special applications. The pulse rate is selected by applying positive power to on of two terminals. Dual Sound Level: 1) Bac-A-Larm rate of 80 bursts per minute, 2) fast pulse rate of 10 bursts per second.
- Model FS255: Fast sounding alarm for special applications requiring a unique sound option. This alarm is capable of quickly demanding attention with sound pulses at 10 bursts per second.
- Mount (Stud): #8-32UNC terminal studs
- Mount (Leads): 18ga 12" (300mm) wire leads. Neg (Blk) Pos (Red)
- Dimensions (200 Series): L 3.25" H 2.64" D 1.6" [82.55 x 67.1 x 40.6mm]
- Dimensions (270): L 3.25" H 2.96" D 1.6" [82.55 x 75.1 x 40.6mm]

### Tech Specs

Amps	ELT248, 1028, 1020, ELT278 and 240CS: 0.2
	270: 1.2
	250: 0.4
	240: 0.23
	230: 0.24
Voltage	ELT248 and 1028: 12-48 VDC
	1020, 270, 250, 240CS and 240 : 12-24 VDC
	ELT278: 12-72 VDC
	230: 12 VDC
Volume	ELT248, 240CS, 240 and 230: 97
	1028: Self-Adjustable 77-97
	1020: Self-Adjustable 77-102
	ELT278: 87
	270: 107
	250: 102
Warranty	2 Years
Temperature Range	-40F to +185F

Part No.	Description
1028	Preco Compact Back-up Alarm Self Adj 77-97 Db 12-48 V Studs
225	Preco Compact Back-up Alarm 87 Db 9-36V Studs
230	Preco Compact Back-up Alarm 97 Db 9-16V Studs
240	Preco Compact Back-up Alarm 97 Db 9-36V Studs
240CS	Preco Night Silent Back-up Alarm 97 Db 9-36V Wire Lead
250	Preco Compact Back-up Alarm 102 Db 9-36V Studs
270	Preco Compact Back-up Alarm 107 Db 9-36V Studs
DS232	Preco Dual Sound Back-up Alarm 97db 9-16V Studs
ELT248	Preco Electric Vehicle Back-up Alarm 97 Db 12-48V Studs
ELT278	Preco Electric Vehicle Back-up Alarm 87 Db 12-72V Studs
ELT280	Preco Electric Vehicle Back-up Alarm 97 Db 12-80V Studs
1020	Preco Compact Back-up Alarm Self Adj 77-102 Db 12-24V Studs

Accessories	Description
200-GS	200-GS Self Grounding Strap to suit 200 Series Back-up Alarm



Authorised Importer and Master Distributor

