

# 7460 Series LED Strobe

## Class I LED Flash Beacon



### Description

The compact 7460 Series Profile™ LED beacon incorporates a simple yet highly effective and tough design featuring an overhead heatsink that allows removal of the flange when the unit is pipe mounted. Eight 3-watt LEDs and a parabolic reflector produce attention getting SAE Class I light output.

The 7460 features a unique Pulse8 flash pattern that human vision is highly sensitive to in the periphery, increasing potential visibility where vehicle hazards are not in direct line of sight. A 5 year warranty and the usual maintenance free, low amp draw benefits of LED technology make this an ideal light for any application.

### Features and Benefits

- Eight 3-watt LEDs and a parabolic reflector.
- Human peripheral vision is highly sensitive to unique Pulse8 flash pattern that features 8 flashes per cycle (80 FPM).
- Overhead heatsink design allows for unobtrusive pipe mounting with flange removed.
- Meets SAE J845 Class I.
- CE, e, IP Rating 67.
- Temperature Range: -22°F to +122°F (-30°C to +50°C).

### Applications

Heavy Equipment, Construction Equipment, Mobile Machinery, Fleet, 4WD.

### Tech Specs

Voltage	12 to 36V DC
Amps	1.0A @ 12V DC
Flash Per Minute	80 FPM
Mount Type	3 Bolt / 1" Pipe
Lens Color	Amber

Part No.	Description
7460R	Model 7460 LED BEACON, 360° RED/RED
7460CG	Model 7460 LED BEACON, 360° CLR/GRN
7460CA	Model 7460 LED BEACON, 360° CLR/AMB
7460B	Mdl 7460 LED BEACON, 360° BLU/BLUE
7460A	Mdl 7460 LED BEACON, 360° AMB/CLR



Authorised Importer and Master Distributor

