# **PreView Sentry Plus Deutsch Kit**

# **Integrated Blindspot Safety System**

Includes: Heavy-duty FMCW 24GHz Sentry Radar, PreView Plus 7" Monitor, 1 camera, 18m / 59' body harness, 9m / 30' Heavy-Duty Body Harness with Deutsch Connectors, 90° Sensor Mounting Bracket





# Description

**Tech Specs** Measuring Performance

| weasuring renormance    |   |
|-------------------------|---|
| Range                   | Prec-configured detection range - see parts table               |
| Range Accuracy          | 0.3m  |
| Azimuth Field of View   | ±75 degrees (10 dBsm target)                                    |
| Elevation Field of View | ±10 degrees (10 dBsm target)                                    |
| Angle Accuracy          | ±2° @ ±10° FOV, ±5 @ ±30° FOV, ±10 @ ±75°<br>FOV                |
| Velocity Range          | ± 9 m/sec (± 20 mph)  |
| Target Resolution       | 1.4 m for static targets, approaching 0.3 m for dynamic targets |
| Cycle Time              | 120 ms (A CAN bus target message is provided in every cycle.)   |
| Water Tightness         | IP 68 - IP 69K  |
| Operating Temp          | -40°C to +60°C  |
| Salt Spray              | ISO 9227  |
| Housing                 | Plastic Aluminum  |
| Lens                    | Hardened glass  |
| Reflector               | Free from reflector   |
| Warranty                | 5 Years   |

#### **Operating Conditions**

| Frequency             | 24.00 – 24.25 GHz                                       |
|-----------------------|---|
| Power Supply          | 9 – 33 VDC, Reverse polarity and over-voltage protected |
| Current               | <0.5 A  |
| Operating Temperature | -40°C to +85°C  |
| Storage Temperature   | -55°C to +105°C   |
| Shock                 | 50G   |
| Vibration             | 25 G, random, all three axis                            |
| Protection Rating     | IP69K   |

#### Operating Modes

| operating modes          |   |  |
|--------------------------|---|--|
| Detection Pattern        | Fixed based on model number                                     |  |
| Target Detection Time    | 300 ms  |  |
| Power On to Active Time  | 300 ms  |  |
| Communications Interface |   |  |
| J1939 CAN Bus            | 250 Kbits/sec, terminated with 120 ohm resistor                 |  |
| LED Interface            | Switch to ground, sink up to 1A, over current protected         |  |
| Physical Characteristics |   |  |
| Sealing                  | IP69K   |  |
| Housing Material         | Polycarbonate radome  |  |
| Dimensions               | 4.90" (w) x 4.06" (h) x 1.28" (d) (12.4 cm x 10.3 cm x 3.25 cm) |  |
| Weight                   | 13 lb (5.9 kg)  |  |
| Mounting                 | Four 0.22" (5.6 mm) diameter mounting holes                     |  |




#### This Preview Sentry Deutsch Kit is a plug-and-play heavy-duty radar solution with a pre-configured sensor range. The kit comes with the FMCW 24GHz Sentry radar sensor, 1 x PreView Plus Camera, 7" colour monitor, 18m / 59' camera extension, 9m / 30' heavy-duty body harness with Deutsch connectors, and a 90° sensor mounting bracket.


## **Features and Benefits**

- · All-in-one Safety System Integrates Vision with Active Blind Spot Detection
- Combines best in class active blind spot detection radar with visual clarification camera and in-cab monitor
- PreView Plus provides operators with a heavy duty, all-in-one safety system by integrating a camera and monitor with Preco's patented radar sensor, operators have a single solution for active blind spot monitoring.

## Applications

#### Heavy-duty object detection





Part No.

PV-PST85043

Description

PreView Sentry Basic System w/ 4.5 x 3mtr sensor range + PreView Plus Camera System Upgrade.





APS Australia

APS: Singapore Chile Perú Brasil





#### **APS USA**

610 Gateway Center Way, Suites J & K San Diego, CA 92102 USA P: 1 619 263 4164 F: 1 619 263 6814

U48 / 9 Vision Street, Wangara, WA 6065 Australia Phone: 61 (8) 9302 2369 Fax: 61 (8) 6305 0047

Colombia

Authorised Importer and Master Distributor