



ECCO[®]

FLEET SOLUTIONS



PRODUCT MIX

 **APS**
LIGHTING & SAFETY
www.aps-supply.com

APS USA
610 Gateway Center Way, Suites J & K
San Diego, CA 92102 USA
P: 1 619 263 4164
F: 1 619 263 6814

APS Australia
U48 / 9 Vision Street,
Wangara, WA 6065 Australia
Phone: 61 (8) 9302 2369
Fax: 61 (8) 6305 0047

APS: Singapore
Mexico
Colombia
Chile
Perú

BE SEEN ON SITE

Lightbars, beacons, minibars, safety directors and directional lights provide an essential layer of safety whether crews are in transit or operating on the work site. A complement of warning lights on fleet vehicles ensures visibility in low-light and extreme weather conditions. Alert and direct on-coming drivers with these performance-optimized signaling devices.

LIGHTBARS



12+ SERIES VANTAGE™
SLEEK, LOW-PROFILE
12-24V | 48 FP | 24-72" Lengths
ICE Optics offer brighter appearance for better visibility
SAE Class I, CA T13, CE, R10, R65



16 SERIES
COMPACT, LOW-PROFILE
12-24V | 31 FP | 22-91" Lengths
Single- or dual-color options | Only 1.6" high
SAE Class I, CA T13



21 SERIES
DELIVERS OFF-ANGLE PERFORMANCE
12V | 31 FP | 22-91" Lengths
Integrated LED Safety Director™
SAE Class I, CA T13, R10



27 SERIES
DELIVERS OFF-ANGLE PERFORMANCE
12V | 31 FP | 22-91" Lengths
Centrally controlled flexibility
SAE Class I, CA T13, R10

BEACONS



7460A
COMPACT, LOW-PROFILE
12-36V | 3.6A | 80 FPMx8
Pulse8 flash pattern
SAE Class I, CE, R10, IP66



7945A
LED BEACON
12-48V | 1.3A | 11 FP
Reinforced polypropylene base
SAE Class II, CE, R10, RoHS



7965A
LED BEACON
12-24V | 3.6A | 11 FP
Aluminum base
SAE Class I, CE, R10, RoHS




EB7185 SERIES
DUAL-COLOR
12-24V | 8.6A | 24 FP
AAA, CAA, CAC, AAA-T13, CAA-T13
SAE Class I, CA T13, R10, IP55, AMECA, RoHS


MINIBARS



5550CA REFLEX™
11" MICROBAR
12-24V | 3.4A | 91 FP
Sync-capable
SAE Class I, CA T13, CE, R10, RCM,
IP65, R65, RoHS



5580A / CA REFLEX™
15" MINIBAR
12-24V | 2.7A | 18 FP
Sync-capable
SAE Class II, CE, R10, IP65, IP69K, RoHS



5585CA REFLEX™
15" MINIBAR
12-24V | 4.6A | 18 FP
Sync-capable
SAE Class I, CA T13, CE, R10, RCM,
IP65, IP69K, RoHS



5590A / CAC REFLEX™
15" MINIBAR
12-24V | 6.0A | 18 FP
Combines reflective and TIR optics
SAE Class I, CA T13, CE, R10, IP65, IP69K



27-DB006-E DUOBEAM™
10" MINIBAR
12V | 6.4A | 19 FP
3 mounting options
SAE Class I, CA T13

SAFETY DIRECTORS™



ED3335A
HIGH-INTENSITY WARNING
12-24V | 49" | 9 FP
8 reflective modules with 20 LEDs
SAE Class I, CE, R10



3410A / 3435A
COMPACT WARNING
12V | 48" | 9 FP
High-intensity with slim design
SAE Class I, CE, R10, RoHS



NASLTS847
TRAFFIC DIRECTOR
12V | 47" | 13 FP
Interior or exterior use
SAE Class I, CA T13



37038AS
HIGH OUTPUT WARNING
12-24V | 46" | 32 FP
High-output warning with low amp draw
SAE Class I



EW3420
COMBO UTILITY BAR
12-24V | 50" | 19 FP
Flood light with Safety Director™
SAE Class I, CA T13

DIRECTIONALS



3510A / C
SURFACE MOUNT
12-24V | 0.7A | 16 FP
In-line waterproof driver
SAE Class I, CA T13 (A only), CE, R10,
IP67, RoHS



ED3703A
SINGLE-COLOR
12-24V | 0.4A | 21 FP
Sync-capable | Steady-burn
SAE Class I, CA T13, R10, R65, IP67, RoHS



ED3704A / AC
SINGLE- & SPLIT-COLOR
12-24V | 0.7A | 30 FP (A), 22 FP (AC)
Sync-capable | Steady-burn
SAE Class I, CA T13, R10, R65, IP67, RoHS



ED3777A / AW
SINGLE- & DUAL-COLOR
12-24V | 1.3A (A), 1.4A (AW)
29 FP (A), 69 FP (AW)
180° warning with work and puddle light
SAE Class I, CA T13 (A only), CE (A only),
R10, R65 (A only), IP67, RoHS



ED5051A / AW
SINGLE- & DUAL-COLOR
12-24V | 0.7A | 29 FP (A), 69 FP (AW)
Sync-capable and dimmable
SAE Class I, CA T13, R10, R65, IP67,
RoHS



ED3701A
SINGLE-COLOR
12-24V | 0.8A | 29 FP
Sync-capable | Ultra low-profile
SAE Class I, CA T13, R10, R65, IP67, RoHS



ED3702AC / AG
DUAL-COLOR
12-24V | 1.25A | 69 FP
Sync-capable | Ultra low-profile
SAE Class I, CA T13, R10, IP67, RoHS



9014A
HIDE-A-LED™
12-24V | 0.9A | 16 FP
Head/tail light or surface mountable
CE, R10, IP67



ED9040A
HIDE-A-LED™
12-24V | 1.2A | 29 FP (Single-Color)
Slim low-profile | All-in-module
SAE Class I, CA T13, R10, R65, IP67, AMECA



ED9040AW
HIDE-A-LED™
12-24V | 0.6A | 69 FP (Dual-Color)
Slim low-profile | All-in-module
SAE Class I, CA T13, R10, R65, IP67,
AMECA



ED3760AW
RUNNING BOARDS, PUSH BUMPERS, TAILGATES
12V | Dual-Color | 32 FP
Universal surface mount capability | Each 12" section offers dual-color
SAE Class II, CA T13, IP67, RoHS



ED9215AW
COMBO WORKLIGHT AND WARNING LIGHT
12-24V | 3.3A | 69 FP
135° warning light with powerful worklight in one unit
SAE Class I, CA T13, R10, IP67, CISPR25, RoHS



EXTEND THE DAY

Worklights, utility bars and interior lighting illuminate the job site, highlight hazards around equipment and make it easier to find tools in the bed or compartments. ECCO's line of white lighting devices offer thousands of hours of service-free operation and feature advanced optics to focus the intense light output. Their rugged and weather-resistant design can withstand tough working conditions to deliver clear and reliable lighting when needed most.

UTILITY BARS



EW3109 / EW3120
SINGLE ROW
12-24V | 9" and 875 Lumens (3109), 20" and 2,175 Lumens (3120)
Flood / Spot Combo | Adjustable end or extrusion mount
CE, IP67, RoHS



EW3214 / EW3225
DOUBLE ROW
12-24V | 14" and 2,800 Lumens (3214), 25" and 4,750 Lumens (3225)
Flood / Spot Combo | Adjustable end or extrusion mount
CE, IP67, RoHS



EW3420
50" COMBINATION UTILITY BAR
12-24V | 50" | 12,600 Lumens
Flood light with Integrated Safety Director™ | Steady burn amber
SAE Class I, CA T13

WORKLIGHTS



E92004
SIX 3-WATT LEDs
12-24V | Flood | 700 Lumens
Polycarbonate lens
CE, R10, IP67, RoHS



E92005
NINE 3-WATT LEDs
12-24V | Flood | 1,000 Lumens
Polycarbonate lens
CE



E92006
NINE 3-WATT LEDs
12-24V | Flood | 1,450 Lumens
Polycarbonate lens
CE, RoHS



E92007
FIVE 3-WATT LEDs
12-24V | Flood | 750 Lumens
Polycarbonate lens
CE, R10



EW2112-DEU
SEVEN 1-WATT LEDs
12-80V | Flood | 1,000 Lumens
Deutsch connector
CE, R10, UL, IP67, RoHS



EW2411
SIX 3-WATT LEDs
12-24V | Flood | 1,000 Lumens
Polycarbonate lens
CE, R10, IP67, RoHS



EW2451
NINE 3-WATT LEDs
12-24V | Flood | 1,300 Lumens
360° rotation axis | Switched
CE, IP67, RoHS



EW2530
SIX 10-WATT LEDs
12-24V | Flood | 3,750 Lumens
Deutsch connector | 120° beam pattern
CE, R10, CISPR25, IP67, IP69K, RoHS



EW3007-F
FOUR 5-WATT LEDs
12-24V | Flood | 1,025 Lumens
3-18 AWG conductor cable
CE, IP67, RoHS



EW3011
TEN 5-WATT LEDs
12-24V | Spot | 5,357 Lumens
360° continuous rotation | 135° tilt range
CE, IP68 (lighthead only)



EW4030
FIFTY-SIX 1.5-WATT LEDs
12-24V | Flood | 4,950 Lumens
Deutsch connector | 170° articulated mount
CE, R10, IP67, RoHS

COMPARTMENT LIGHTING



EW0134
LED STRIP LIGHTING
12V | 25" Strip | 200 Lumens
Spliceable
CE, IP67, RoHS



EW0117
LED STRIP LIGHTING
12V | 24" Strip | 700 Lumens
Spliceable
CE, IP65, RoHS



EW0111
LED STRIP LIGHTING
12V | 36" Strip | 1,400 Lumens
Spliceable
CE, IP65, RoHS



EW0200
SURFACE MOUNT
12-24V | 0.4A | 425 Lumens
Flood | Switched
CE, RoHS



EW0204
SURFACE MOUNT
12-24V | 0.8A | 750 Lumens
Flood | PIR Motion Sensor
R10, IP67, RoHS



EW0205
SURFACE MOUNT
12-24V | 0.8A | 750 Lumens
Flood
R10, IP67, RoHS



EW0600
SURFACE MOUNT
12-24V | 18" | 2,000 Lumens
Flood | Switched
CE, RoHS



EW0700
SURFACE MOUNT
12-24V | 13" | 400 Lumens
Flood | Switched | Pivotal
CE, RoHS



EW0701
SURFACE MOUNT
12-24V | 21.5" | 1,250 Lumens
Flood | Switched | Pivotal
CE, RoHS



EW0801
90° CORNER MOUNT
12-24V | 21.5" | 400 Lumens
Flood | Concealed fasteners
CE, IP67, RoHS



REDUCE RISK WITH REVERSING SAFETY

Maneuvering around the job site and the yard present unique safety challenges. Equipping dependable back-up alarms and camera systems minimize those risks; protecting crews and pedestrians alike. ECCO was the first to introduce commercial back-up alarms and these time-tested devices are designed to consistently operate at peak performance.

ALARMS



510
SURFACE MOUNT
12V | 97dB | 0.2A
Compact size | Self grounding
SAE Type C, CE, R10, UL, IP65, AMECA



530
SURFACE MOUNT
12-24V | 102dB | 1.0A
Compact size | Self grounding
SAE Type F, CE, R10, UL, IP65, AMECA



SA950
SURFACE MOUNT
12-24V | 82-102dB | 0.4A
Smart Alarm® | Self grounding
CE, R10, UL, IP65



575
SURFACE MOUNT
12-24V | 107dB | 0.9A
Compact size
SAE Type B, CE, R10, UL



SA901N
SURFACE MOUNT
12-24V | 82-107dB | 0.3A
Smart Alarm® | Sealed in epoxy
CE, R10, UL, IP64



EA5200
SURFACE MOUNT
12-24V | 97dB | 1.0A
Multi-Frequency™ Alarm
SAE Type C, CE, R10, RCM, AMECA



EA9724
SURFACE MOUNT
12-24V | 77-97dB | 0.7A
Smart Alarm® | Multi-Frequency™ Alarm
SAE Type F, CE, R10, IP64

CAMERA SYSTEMS



K7000B GEMINEYE™
7" LCD COLOR SYSTEM
18 Infrared LEDs | Sunshade Included
Two camera expandable
FCC (camera only), CE,
IP69K (camera only), RoHS



EC5603-K GEMINEYE™
5.6" LCD COLOR SYSTEM
Soft touch buttons on monitor
Three camera expandable
FCC, CE, R10, RCM,
IP69K (camera only), RoHS



EC4200-K GEMINEYE™
4.3" LCD COLOR MIRROR SYSTEM
Integrated mirror | Flush mount camera
Two camera expandable
FCC, CE, IP67 (camera only), RoHS

THE ECCO CARE PROMISE

ECCO is known the world over as the premier commercial warning and safety products manufacturer. Our reputation for excellence is rooted in an unwavering commitment to protecting your most important asset—your people. Helping them do their jobs safely and efficiently drives us to exceed the most rigorous engineering and service standards.

Each day, we hold ourselves accountable to the ECCO Care Promise—excellent customer service, superior products, the industry's fastest lead times, customization and a no-hassle warranty.

NO-HASSLE WARRANTY

Introducing **ECCO's 5-Year, No-Hassle Warranty** covering a wide range of safety solutions. Exceptions apply to a limited amount of products:

- Replacement parts and accessories (1 year)
- Camera systems (1 year)
- Light-duty and driver-based alarms (2 years)
- Halogen, strobe beacons and minibars (1 year)
- Non-permanent mount products such as EW2461 (1 year)

Visit www.ecco.esg.com for additional product details.

THE ECCO CARE PROMISE ENSURES that our products and our people perform to a higher standard—so that you can, too. Look to ECCO for reliability when you need it most.





APS USA
610 Gateway Center Way, Suites J & K
San Diego, CA 92102 USA
P: 1 619 263 4164
F: 1 619 263 6814

APS Australia
U48 / 9 Vision Street,
Wangara, WA 6065 Australia
Phone: 61 (8) 9302 2369
Fax: 61 (8) 6305 0047

APS: Singapore
Mexico
Colombia
Chile
Perú