

Vision X Shocker X2 LED Light Bar

Dual Row Light Bar Series



Front Bumpers | 10"



Hood, Front Bumpers | 20"



Stock RZR Cage | 32"



Aftermarket RZR Cage,
Can-Am Cage, Mid Size Truck Roof | 40"



Full Size Roof | 51"



BROAD
SPOT
BEAM



Description

The all-new Vision X Shocker X2 LED Light Bar packs two rows of Vision X's patented Iris Reflectors with 5W ultra-bright LEDs to produce a wide and long-distance beam pattern that is prime for turning any night-time adventure into daylight. The dual row LEDs means doubling the output when compared to most single row LED light bars, therefore making the Shocker X2 the newest and brightest addition to the Vision X LED light bar range.

Constructed out of 6061 extruded aluminium, the oversized heatsink housing design ensures that the Shocker X2 will maintain maximum output even after prolonged use. Equipped with a GORE® pressure relief valve and moisture block membrane, the Shocker X2's internals are completely protected from water and dust ingress (IP68 and IP69K Rated).

The Vision X Shocker X2 also features a smooth back-lit halo function that off-road lights are known for and can be used as a daytime running light or parking light for added style. Available in 10" to 51" (25.4cm to 129.5cm) lengths, each bar will include a complete wiring harness, heavy-duty wing mounts, and is backed by Vision X's lifetime warranty.

Features and Benefits

- **High Output CREE LEDs:** The 5W XT-E HE LED from Cree coupled with Iris Reflectors is what allows the Shocker X2 to project light up to 885m (2,905 ft).
- **Dual Mounting Standard:** Each Shocker X2 Light Bar includes side wing mounts and Vision X's patented mounting feet to accommodate any mounting points.
- **Smooth Backlit Halo:** The Shocker X2 comes equipped with a back-lit halo that can be used as a daytime running light or parking light.

Applications

Mining Light Vehicles (LV's), Service Vehicles, Automotive, Off-road, 4x4, 4WDs

Tech Specs

Type	5W XT-E HE High Output CREE LEDs
Beam Pattern	Broad Spot
rLumens	6,420 Lu (SHK-X2BH2.6), 16,050 Lu (SHK-X2BH2.15), 25,680 Lu (SHK-X2BH2.24 - 32"), 32,100 Lu (SHK-X2BH2.30), 34,240 Lu (SHK-X2BH2.39)
Beam Distance	1,210 ft / 368.8m (SHK-X2BH2.6), 1,770 ft / 539.5m (SHK-X2BH2.15), 2,495 ft / 760.5m (SHK-X2BH2.24), 2,820 ft / 859.5m (SHK-X2BH2.30), 2,905 ft / 885.4m (SHK-X2BH2.39)
Voltage	9-32V DC
Watts	60W (SHK-X2BH2.6), 150W (SHK-X2BH2.15), 240W (SHK-X2BH2.24), 300W (SHK-X2BH2.30), 320W (SHK-X2BH2.39)
Amps	5A @ 12V DC (SHK-X2BH2.6), 12.5A @ 12V DC (SHK-X2BH2.15), 20A @ 12V DC (SHK-X2BH2.24), 25A @ 12V DC (SHK-X2BH2.30), 26.67A @ 12V DC (SHK-X2BH2.39)
Operating Temperature	-40°C to +80°C
Rating	IP68, IP69K
Housing	Extruded 6061 Aluminium
Mounting / Hardware	Mounting hardware, wiring harness, relays, lighted rocker switch
Lengths (accurate)	9.57" / 24.3cm (SHK-X2BH2.6), 20.9" / 53.1cm (SHK-X2BH2.15), 32.24" / 81.9cm (SHK-X2BH2.24), 39.8" / 101.1cm (SHK-X2BH2.30), 50.98" / 129.5cm (SHK-X2BH2.39)
Dimensions (DxLxH)	3.82" / 97mm Depth x (Lengths as above) x 3.82" / 97mm High
Warranty	Vision X Limited Lifetime Warranty

Part No.	Description
SHK-X2BH2.6	10" Shocker X2, 6,420 rLu, 1,210 ft beam, 60W, 5A, Broad Spot (VX No. 2610216)
SHK-X2BH2.15	20" Shocker X2, 16,050 rLu, 1,770 ft beam, 150W, 12.5A, Broad Spot (VX No. 2620216)
SHK-X2BH2.24	32" Shocker X2, 25,680 rLu, 2,495 ft beam, 240W, 20A, Broad Spot (VX No. 2630216)
SHK-X2BH2.30	40" Shocker X2, 32,100 rLu, 2,820 ft beam, 300W, 25A, Broad Spot (VX No. 2640216)
SHK-X2BH2.39	51" Shocker X2, 34,240 rLu, 2,905 ft beam, 320W, 26.7A, Broad Spot (VX No. 2650216)



Authorised Importer and Master Distributor

